





SINGLE RAIL POSITIONING STAGE SPECIFICATIONS		
Motor P/N	BLDM-B04	
Stroke	16.0 in	406.4 mm
Encoder Resolution	1 micron	
Bearing Type	Recirculating Ball	
Moving Mass	2.75 lbs	1.25 kg
Total Mass	16.0 lbs	7.3 kg
Resistance @ 20C	6.4 ohms	
Inductance @ 20C	4.0 mH	
Electrical Time Constant	1.0 msec	
Motor Constant	1.17 LBS/SQRT(Watt)	5.2 N/SQRT(Watt)
Force Constant	3.0 LBS/Amp	13.2 N/Amp
Back EMF	0.34 V/ips	13.2 V/m/sec
Force @ 100% Duty	6.2 lbs	27.8 N
Power @ 100% Duty	39.3 watts	
Current @ 100% Duty	2.1 amps	
Force @ 10% Duty	18.7 lbs	83.3 N
Power @ 10% Duty	353.7 watts	
Current @ 10% Duty	6.3 amps	
Stage Length	25.30 in	643 mm
Stage Width	5.13 in	130.3 mm
Stage Height	3.93 in	99.8 mm

5

40-0394

SHEET 3 of 3

D

ONLY

Single Rail Positioning Stage Model #:

SRS-016-05-013-01-EX MATERIAL FINISH DATE 8-29-17